

# H5



SCAN ME 01-19-2024 .V1 WHERE CUSTOMER SERVICE AND QUALITY IS OUR PRIORITY!

Visit our website: www.herreroandsons.com or scan the QR code

#### WHEEL ACCESSORIES



#### **PLASTIC & CHROME. TIRE VALVE CAPS**

#### **ALUMINUM. TIRE VALVE CAPS**



5 PC Set





43.820 Black Plastic (5)



43.825 Chrome Metal (5)

24 SETS INNER PACK / 144 SETS MASTER PACK



Set



43.840 Black (4)



Anodized Blue (4)



Anodized Red (4)



43.845 Chrome (4)



43.860 Black (4)



43.862 Anodized Blue (4)



43.863 Anodized Red (4)



43.865 Chrome (4)

24 SETS INNER PACK / 144 SETS MASTER PACK

#### ANTIFREEZE / COOLANT



29.858-4 Antifreeze/Coolant (Pink) Ready Mix 50/50, 1 Gallon 4 PER CASE / 52 CASES PER PALLET

HEAVY DUTY HS READY MIX 50/50 PREDILUTED ANTIFREEZE/ COOLANT is an ethylene glycol based product that provides year-round protection against freeze-ups, boilovers and corrosion under extreme conditions. HS Ready Mix 50/50 Prediluted Antifreeze/Coolant has an expected service life of 5 years or 150,000 miles in automobiles and other light-duty and heavy-duty vehicles (vans, pick-ups, SUV's etc.). HS Ready Mix protects against freeze-ups down to -34° F. HS Ready Mix protects against boil-overs up to 265° F. A full range of inhibitors protect all cooling system metals and will not damage auto finishes or rubber parts. The Antifreeze meets ASTM D 3306 (Automotive Prediluted Antifreeze). ASTM D 4985 (Heavy-Duty Prediluted Antifreeze) and ASTM D 6210 (Heavy-Duty Prediluted, Fully-Formulated Antifreeze). It also meets or exceeds the following industry specifications as a concentrated or prediluted antifreeze/coolant. The Maintenance Council of the American Truck Association. Antifreeze also meets the non-phosphate requirements of European OEM's and non-silicate requirements of Japanese OEM's. Meets: ASTM D3306, JIS K2234.

HS Ready Mix 50/50 is recommended for use in:

- Toyota
- Lexus
- KIA
- Honda/Acura
- Mitsubishi
- Subaru
- Daewoo Hyundai
- Nissan/Infiniti
- Mazda
- Suzuki
- Daihatsu
- Scion
- Isuzu

HS 50/50 Protection Premix Freeze-Up -34°F **Protection Boil-Over** +265°F **Protection** 



POAT (Phosphate Organic Acid Technology)

The above registered trademarks are owned by third parties.

\* The Maintenance Council of the American Trucking Assoc. Antifreeze also meets the non-phosphate requirements of European OEM's and non-requirements of Japanese OEM's.







#### STEERING WHEEL LOCK





- · Highly visible yellow color distracts thieves from break-ins.
- · Self locking mechanism.
- The key is only needed to unlock the device.
- Allows the driver to enter or leave the vehicle easily.
- Tough hardened steel construction.
- Foam coated to protect the steering wheel against damage.
- Includes 2 keys.



Space Left Empty For **FUTURE PRODUCTS** 









# Telescopic Water Brush


28.488

Bi-level, Soft Bristles Telescopic Water Brush 12 PER MASTER PACK

- Adjusts from 4' 6" (1.37m) to 8' (2.44m) in length.
- Built-in, Easy On/Off Water Flow Switch.
- Corrosion Resistant Telescopic Aluminum Pole.
- Ergonomic Grips.
- 10" x 6" Wide Brush with Premium Quality Soft Bristles.



#### **Microfiber Drying Towel**



Waffle Design Absorbs More Water





- Super Absorbant Waffle Design
- Holds More Water
- Spot & Streak Free
- Lint & Scratch Free
- Reduces Drying Time



28.324
Microfiber
Drying Towel
Large 24" x 24"
1PC Pack
20 PER MASTER PACK



28.336
Microfiber
Drying Towel
X-Large 36" x 36"
1PC Pack
20 PER MASTER PACK



#### 2 Pcs 5" Microfiber Applicator Pads




2 Pcs Pack



Ideal For Applying:

- Polishes
- Waxes
- Protectants
- Tire Shine



28.352 5" Microfiber **Applicator Pads** 2 Pcs Pack 48 PER MASTER PACK

#### 7 Pcs Wash & Detailing Kit



(1) Two sided Chenille Wash Mitt



(1) Microfiber Drying Towel 24"x 24"



(3) Microfiber Cloths 12" x 16"



(1) 5" Microfiber **Applicator Pads** 

305.885.7922



(1) Storage Case

28.307 7 Pcs Wash & Detailing Kit 24 PER MASTER PACK



# PERFORMANCE WINDOW FILMS



MADE IN THE USA



### Safety / Solar Security "A" Grade Film Scratch-Resistant

Professional grade deep-dyed layer films offer the same protection as the clear security films but also provide heat and glare reduction for increasingly popular automotive and building applications. Film has extra strong, UV-Protected, PS adhesive and a scratch resistant coating. We only use Dupont Teijin® polyester because it is the best quality polyester for safety in the market. Large amount of adhesive on this safety film allow us to surpass American & European standards of impact, shatterproof & drop ball tests.

#### **Clear Security Film**



#### Dyed Security Film



#### DYED SECURITY FILM

(152.4 cm x 30.5 m) 60" x 100'

			VLI	ISER	My
14.XSA15CSR4	Charcoal	4 mil	<del>17</del> %	43% /	15 ENEW S
14.XSA35CSR4	Charcoal	4 mil	35%	34% 🖊	<b>5</b>
14.XSA50CSR4	Charcoal	4 mil	50%	29%	<b>5</b>
SA15CHSRPS4	Charcoal	4 mil	17%	43% LL	MEW Z
					<b>~~</b>

# CERAMIC WINDOW FILMS HIGHER & BEAT PLANTON PLANTON BRANCH BRANCH STATE PARTY OF THE PARTY OF T

## Professional "A" Grade HS IR Nano-Ceramic, Scratch Resistant, Non-Reflective, Non-Metalized, High Heat & UV Rejection

NANO-Ceramic Films, by Herrero & Sons Corp, ensure no signal interference from popular devices such as radios, GPS, key-less entry, cell phones and navigation devices. The unique technology used to produce HS IR Nano-Ceramic makes it the most state-of-the-art automotive film today. The Film provides a proprietary non-metalized, non-conductive Nano-ceramic technology with maximum heat and ultraviolet rejection, excellent optical clarity, and scratch and corrosion-resistant properties. HS IR Nano-Ceramic, dramatically reduce irreversible damage to human skin and vehicle interiors due to harmful ultraviolet (UV), visible, and infrared (IR) rays that penetrate ordinary window glass, while keeping the vehicle significantly cooler. In other words, practically clear films reject high levels of heat as dark films do. HS IR Nano-Ceramic, are light enough to meet visible light transmission laws for windscreens in most countries worldwide and provide the ultimate in comfort and protection as well as an elegant image. Installed HS IR Nano-Ceramic, help maintain temperature in interior surfaces of vehicles, offices or homes up to a maximum of 16°C (30°F) much cooler than in comparison with unprotected glass. This reduction in temperature increases the comfort but also reduces the use of air conditioners, helping to reduce energy costs and fuel consumption. Installer friendly films are easily heat-formed and have PS mounting adhesive for rapid install on curve automotive glass.

	5%	15%	30%	70%
Color Darkness	5%	15%	30%	70%
Heat Rejection	97%	89%	79%	61%
<b>코</b> Infrared	90%	90%	90%	90%
Ultraviolet	99%	99%	99%	99%





#### IR NANO-CERAMIC FILM (152.4 cm x 30.5 m) 60" x 100'

			<u>VLI</u>	IPER	Reject	<u>Cut</u>
14.9605	Ceramic Black	2.3Mil	5%	97%	90%	99%
14.9615	Ceramic Black	2.3Mil	15%	89%	90%	99%
14.9630	Ceramic Black	2.3Mil	30%	79%	90%	99%
14.9670	Ceramic Blue	2.3Mil	70%	61%	90%	99%















UV

130°F

Without HS IR Nano-Ceramic Window Film

100°F Protected by HS IR Nano-Ceramic Window Film



# ® *5CRATCH RESISTANT* PERFORMANCE

SMOKE

IDEAL FOR AUTO, VANS, RV, TRUCKS, HOME, OFFICE, BOATS, ETC...

#### DIY STANDARD WINDOW FILM KIT



		5%	20%	35%
VLT	Color Darkness	5%	20%	35%
TSER	Heat Rejection	54%	43%	39%



#### **DYED FILM 20" x 10'** (50 cm x 3m)

	CINICIVE	<u>VLI</u>	IULII
14.305	Very Dark Smoke	5%	54%
14.320	Dark Smoke	20%	43%
14.335	Medium Smoke	35%	39%
	CHARCOAL / BLACK	<u>VLT</u>	<u>TSER</u>
14.805	Very Dark Charcoal / Black	5%	54%
14.820	Dark Charcoal / Black	20%	43%
14 835	Medium Charcoal / Black	35%	39%

- Scratch Resistant
- Pressure Sensitive Adhesive
- Blade & Squeegee Included
- 99% UV Rays Rejected
- 1.2 Mil

**ENERGY** 

**TSFR** 

10 KITS PER MASTER PACK



**SAVES** 

99% UV RAYS









#### DIY CERAMIC WINDOW FILM KIT



		5%	[15%]	30%
۲۲	Color Darkness	5%	15%	30%
TSER	Heat Rejection	86%	71%	62%



Does Not Interrupt Radio, GPS Frequency

# WINDOW FILMS

#### **CERAMIC FILM 30" x 10' (76cm x 3m)**

	CERAMIC	<u>VLT</u>	<u>tser</u>
14.705	Ceramic Black	5%	86%
14.715	Ceramic Black	15%	71%
14.730	Ceramic Black	30%	62%

- Scratch Resistant
- Pressure Sensitive Adhesive
- Blade & Squeegee Included
- 99% UV Rays Rejected
- High Heat Rejection
- 2.3 Mil















10 KITS PER MASTER PACK

130°F

Without Ceramic Window Film

100°F

Protected with Ceramic Window Film

VIT: VISIBLE LIGHT TRANSMITANCE TSER: TOTAL SOLAR ENERGY REJECTED













#### INCREASE SAFETY & VISIBILITY IN ANY WEATHER

One bulb contains 2 colors. You can switch from white light to yellow whenever you want by simply turning ON/OFF/ON within 5 seconds.

- Plug and Play / Hassle Free Installation
- Perfect Lighting Beam Pattern
- Built-In 11,000 RPM Turbo Cooling Fan
- Built-In Smart IC Driver
- Built-In CANBUS Decoder

- Double-Sided (1860 Chip)
- Aviation Aluminum Housing
- 10,000 LM Per Double-Sided Set
- IP68 Water-Proof Rate
- Working Temp: -40°C +80°C



**63.LEDH1WY** (H1)



**63.LEDH7WY** (H7)



**63.LEDH11WY** (H11)



**63.LED9005WY** (9005) (H10) (HB3)



**63.LED9006WY** (9006, HB4)

50 PER MASTER PACK